



Standard Hollow Tine - .750MT x 5.750L x .660OD R104-0984



Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

Replaces

| | |
|--------------|--------------------|
| R&R Products | R100-3635 |
| Toro | 100-3635, 104-0984 |

Specifications

| | |
|----------------------------------|------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Standard Hollow |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 5.75 in (146mm) |
| D - Tine Tip Outside (Hole) Dia. | .660 in (16.8mm) |
| E - Tine Tip Inside (Core) Dia. | .500 in (12.7mm) |
| F - Tine Wall Thickness | .062 in (1.6mm) |
| Savings | Volume Buy |

Fits Models

- Toro Fairway Aerator
- Toro ProCore 1298
- Toro ProCore 440
- Toro ProCore 648
- Toro ProCore 660
- Toro ProCore 864
- Toro ProCore 880
- Toro ProCore 648s

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>