



Alloy Machined Side-Eject Tine - .472MT x 12.000L x .680OD R9990040



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

R&R Products	RC10755
--------------	---------

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.472 in (11.9mm)
C - Tine Length	12 in (305mm)
D - Tine Tip Outside (Hole) Dia.	.680 in (17.3mm)
E - Tine Tip Inside (Core) Dia.	.460 in (11.7mm)
F - Tine Wall Thickness	.110 in (2.8mm)

Fits Models

Redexim Verti-Drain
Southern Green Soil Reliever

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>