



Alloy Machined Side-Eject Tine - .472MT x 6.000L x .410OD R1191935



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treatment facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

| | |
|----------------------------------|---------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject |
| B - Tine Mounting Dia. | .472 in (11.9mm) |
| C - Tine Length | 6 in (152mm) |
| D - Tine Tip Outside (Hole) Dia. | .410 in (10.4mm) |
| E - Tine Tip Inside (Core) Dia. | .250 in (6.4mm) |
| F - Tine Wall Thickness | .078 in (2.0mm) |

Fits Models

Wiedenmann Aerator

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>