



Alloy Machined Side-Eject Tine - .375MT x 4.000L x .350OD R100-3625



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

Toro 100-3625

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.375 in (9.5mm)
C - Tine Length	4 in (102mm)
D - Tine Tip Outside (Hole) Dia.	.350 in (8.9mm)
E - Tine Tip Inside (Core) Dia.	.236 in (6mm)
F - Tine Wall Thickness	.062 in (1.6mm)
Savings	Volume Buy

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>



Alloy Machined Side-Eject Tine - .375MT
x 4.000L x .350OD
R100-3625



Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>