



Alloy Machined Side-Eject Tine - .750MT x 5.500L x .550OD R201536



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	5.500 in (140mm)
D - Tine Tip Outside (Hole) Dia.	.550 in (13.9mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.065 in (1.7mm)

Fits Models

John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>



Alloy Machined Side-Eject Tine - .750MT
x 5.500L x .550OD
R201536



Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>