



Alloy Machined Side-Eject Tine - .500MT x 4.500L x .460OD R201636



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

R&R Products R112-1316, R112-1322

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.500 in (12.7mm)
C - Tine Length	4.5 in (114mm)
D - Tine Tip Outside (Hole) Dia.	.460 in (11.7mm)
E - Tine Tip Inside (Core) Dia.	.330 in (8.4mm)
F - Tine Wall Thickness	.070 in (1.8mm)

Fits Models

Jacobsen Aero King 30
Jacobsen GA-24
Ryan GA30

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>



Alloy Machined Side-Eject Tine - .500MT
x 4.500L x .460OD
R201636



Ryan Greensaire II

Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS
353 87 632 9827

<https://golfmech.rrproducts.com/>