



# Alloy Machined Side-Eject Tine - .625MT x 6.000L x .640OD R339108



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treatment facility. Very popular for the multiple tine holders which fit all greens aerators.

## Replaces

Jacobsen 339108

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.625 in (15.9mm)
C - Tine Length	6 in (152mm)
D - Tine Tip Outside (Hole) Dia.	.640 in (16.3mm)
E - Tine Tip Inside (Core) Dia.	.500 in (12.7mm)
F - Tine Wall Thickness	.062 in (1.6mm)

## Fits Models

Jacobsen Aero King PT2448  
Jacobsen Aero King T1224  
Jacobsen Verator VA-24

## Golfmech Ltd

Hullaghfin Balrath Navan, C15 VOFS  
353 87 632 9827

<https://golfmech.rrproducts.com/>